
HEAD DIMENSIONS

Wafer: Phillips & Square Recess


#8 & 10 Diam: 150°, ±2° #12 & 1/4 Diam: 140°, ±2°






Wafer Phillips Head for Self-Drilling Screws												
Nominal Size	A Head Diameter		R Recess Diameter		I Recess Depth		W Wafer Thickness		Bottom Countersink Angle	Phillips Driver Size		
											Max.	Min.
	8	.380	.359	.189	.176	.110	.086	.035	.025	50°	2	
10	.516	.441	.204	.190	.124	.101	.040	.031	60°	2		
12	.552	.511	.268	.254	.139	.115	.040	.031	70°	3		
1/4	.620	.580	.282	.267	.160		.042	.033	70°	3		

NOTE: There is no single standard for Wafer head dimensions. These values are offered as a guide; deviations from these specifications may occur





Wafer Square Recess Head for Self-Drilling Screws											
Nominal Size	Α		М	I		w		С	Phillips Driver Size		
	Head Diameter		Recess Width	Recess Denth		Wafer Thickness		Bottom Countersink Angle			
	Max.	Min.	Ref	Max	Min	Max	Min	± 2°			
12	.551	.512	.133	.095	.080	.039	.031	70°	3		

NOTE: There is no single standard for Wafer head dimensions. These values are offered as a guide; deviations from these specifications may occur